
Impulse® 1012 8 ohm - Black



OVERVIEW

Ultra-high performance from a weather-resistant, two-way (full-range or bi-ampable) speaker system that will provide up to 133 dB SPL. This system provides high power handling capability while maintaining a smooth, yet clear response. The elegant and durable trapezoidal enclosure is made of high-impact polypropylene with a metal grille. This system is comprised of a 12 inch Black Widow® woofer with a Kevlar® impregnated cone (with a specially treated surround) and a RXTM 22 two inch titanium compression driver coupled to a constant directivity horn with Sound GuardTM high frequency driver protection. Connections are made via two parallel 1/4 inch phone jacks for daisy-chaining and a switchable 4-pin Neutrik® Speakon® connector. This system will provide up to 133 dB SPL and can be used on the floor, speaker stand or be flown via top and bottom flying points.

FEATURES

- 1000 watt, 2-way weather resistant enclosure with molded-in stand adapter and flying points on the top and bottom
- One 12 inch Black Widow® woofer (1208-8 SPS BWX)
- RXTM 22 compression driver coupled with a molded-in 90 degree x 45 degree constant directivity horn
- Sound GuardTM high frequency driver protection circuit
- Available in black and white
- Response: 72 Hz to 18 kHz
- Sensitivity: 99 dB (1W at 1m)
- Impedance: 8 ohms
- Weight Unpacked: 44.60 lb(20.23 kg)
- Weight Packed: 50.00 lb(22.68 kg)
- Width Packed: 21.25"(53.975 cm)
- Height Packed: 27.25"(69.215 cm)
- Depth Packed: 17.37"(44.1198 cm)