

Pro-LITE™ Series

Lightweight Power Amplifiers

CREST
AUDIO®

Pro-LITE 7.5 | Pro-LITE 5.0 | Pro-LITE 3.0 | Pro-LITE 2.0



Description

Featuring an efficient design and built on the solid, three-decade legacy of Crest Audio amplifiers, the Pro-LITE® Series power amps provide high power and rock solid performance in an ultra-efficient lightweight package for all professional audio applications. The Crest Audio Pro-LITE amplifiers are designed with an advanced, high-speed class D design with a switch-mode power supply that reduces weight while increasing reliability, thermal efficiency and output power in parallel, stereo and bridged modes.

Features

- Parallel/Bridge/Stereo mode switch
- ACL™ Automatic Clip Limiting protection
- Revolutionary Pro-LITE class D topology
- Detented input controls
- Combi Neutrik® XLR 1/4" inputs
- Speakon output connectors
- XLR thru connector
- Two channel-independent fourth order crossovers



Pro-LITE™ Series Amplifiers

Specifications

	Pro-LITE™ 7.5	Pro-LITE™ 5.0	Pro-LITE™ 3.0	Pro-LITE™ 2.0
Rated Watts 2ch x 2 ohms	4800 watts 20ms repetitive burst / 3790 watts 1% THD both channels driven @ 1kHz	3300 watts 20ms repetitive burst / 2600 watts 1% THD both channels driven @ 1kHz	1820 watts 20ms repetitive burst / 1500 watts 1% THD both channels driven @ 1kHz	1100 watts 20ms repetitive burst / 900 watts 1% THD both channels driven @ 1kHz..
Rated Watts 2ch x 4 ohms	2810 watts 20ms repetitive burst / 2450 watts 1% THD / 2030 watts 0.15% THD, both channels driven @ 1kHz	2025 watts 20ms repetitive burst / 1725 watts 1% THD / 1500 watts 0.2% THD, both channels driven @ 1kHz	1000 watts 20ms repetitive burst / 900 watts 1% THD / 830 watts 0.15% THD, both channels driven @ 1kHz	600 watts 20ms repetitive burst / 570 watts 1% THD / 530 watts 0.15% THD, both channels driven @ 1kHz
Rated Watts 2ch x 8 ohms	1550 watts 20ms repetitive burst / 1425 watts 1% THD / 1200 watts 0.15% THD, both channels driven @ 1kHz	1175 watts 20ms repetitive burst / 1000 watts 1% THD / 825 watts 0.2% THD, both channels driven @ 1kHz	540 watts 20ms repetitive burst / 500 watts 1% THD / 450 watts 0.15% THD, both channels driven @ 1kHz	370 watts 20ms repetitive burst / 325 watts 1% THD / 300 watts 0.15% THD, both channels driven @ 1kHz
Minimum Load Impedance	2 ohms	2 ohms	2 ohms	2 ohms
Maximum RMS Voltage Swing	124 volts	105 volts	71 volts	56 volts
Frequency Response	20 Hz - 25 kHz; +0dB, -3dB	20 Hz - 22kHz; +/- 0.5dB at 1 watt	20 Hz - 28kHz; +0dB, -3.0dB @ 1 watt	10 Hz - 30kHz; +/- 3 dB at 1 watt, 8 ohms
20Hz - 20kHz 2 ch x 2 ohms	<0.5% @ 3390 watts 20Hz to 4kHz, decreasing to 3100 watts @ 20kHz, both channels driven	<0.5% @ 2250 watts 20Hz to 4kHz, decreasing to 1650 watts @ 20kHz, both channels driven	<0.5% @ 1350 watts 20Hz increasing to 1380 watts at 20kHz, both channels driven	<0.25% @ 800 watts 20Hz to 4kHz, decreasing to 760 watts @ 20kHz, both channels driven
20Hz - 20kHz 2 ch x 4 ohms	<0.15% @ 1850 watts 20Hz to 20kHz, both channels driven	<0.15% @ 1400 watts 20Hz to 10kHz, decreasing to 1350 watts @ 20kHz, both channels driven	<0.15% @ 800 watts at 20Hz increasing to 850 watts at 20kHz, both channels driven	<0.15% @ 540 watts 20Hz to 20kHz, both channels driven
20Hz - 20kHz 2 ch x 8 ohms	<0.15% @ 1170 watts 20Hz to 20kHz, both channels driven	<0.15% @ 860 watts 20Hz to 4kHz, both channels driven	<0.15% @ 450 watts 20Hz increasing to 500 watts at 20kHz, both channels driven	<0.15% @ 300 watts 20Hz to 20kHz, both channels driven
Input CMRR	< -75 dB at 1kHz	< -75 dB at 1kHz	< -76 dB at 1kHz	< -69 dB at 1kHz
Voltage Gain	x 40 (+32 dB)	x 40 (+32.0 dB)	x 75 (+37 dB)	x 60 (+35 dB)
Crossover	100 Hz switchable 2nd order high pass and 3rd low pass per channel			
Hum and Noise	> -100dB, "A" weighted reference to rated power @ 4 ohms	> -105dB, "A" weighted reference to rated power @ 4 ohms	> -100dB, "A" weighted reference to rated power @ 4 ohms	> -100dB, "A" weighted reference to rated power @ 4 ohms
Slew Rate	> 12V/µs	> 12V/µs	> 12V/µs	> 12V/µs
Damping Factor (8 ohms)	>200:1 @ 20 Hz - 1 kHz @ 8 ohms	>210:1 @ 20 Hz - 1 kHz @ 8 ohms	>255:1 @ 20 Hz - 1 kHz @ 8 ohms	>170:1 @ 20 Hz - 1 kHz @ 8 ohms
Input Sensitivity	2.25V +/- 3% for 1kHz 4 ohm rated power, 2.2V +/- 3% for 1kHz 2 ohm rated power	1.95V +/- 3% for 1kHz 4 ohm rated power, 1.83V +/- 3% for 1kHz 2 ohm rated power	.740V +/- 3% for 1kHz 4 ohm rated power, .710V +/- 3% for 1kHz 2 ohm rated power	.775V +/- 3% for 1kHz 4 ohm rated power, .35V +/- 3% for 1kHz 2 ohm rated power
Input Impedance	20 kilohms, balanced and 10 kilohms unbalanced	20 kilohms, balanced and 10 kilohms unbalanced	15 kilohms, balanced and 7.5 kilohms unbalanced	15 kilohms, balanced and 7.5 kilohms unbalanced
Current Draw @ 1/8 in VA (watts):	2210 (1440) @ 2 ohms, 1550 (950) @ 4 ohms, 985 (560) @ 8 ohms	1435 (890) @ 2 ohms, 920 (525) @ 4 ohms, 625 (335) @ 8 ohms	960 (540) @ 2 ohms, 620 (320) @ 4 ohms, 400 (190) @ 8 ohms	540 (315) @ 2 ohms, 370 (185) @ 4 ohms, 240 (115) @ 8 ohms
Current Draw @ 1/3 in VA (watts):	4260 (3150) @ 2 ohms, 3120 (2160) @ 4 ohms, 1890 (1200) @ 8 ohms	3050 (2155) @ 2 ohms, 1880 (1200) @ 4 ohms, 1200 (715) @ 8 ohms	2070 (1310) @ 2 ohms, 1220 (700) @ 4 ohms, 740 (400) @ 8 ohms	1250 (760) @ 2 ohms, 750 (425) @ 4 ohms, 460 (240) @ 8 ohms
Idle Consumption:	250VA, 120 watts	195VA, 90 watts	140VA, 40 watts	90VA, 40 watts
Cooling	3 temperature dependent variable speed fans	3 temperature dependent variable speed fans	temperature dependent variable speed fan	temperature dependent variable speed fan
CONTROLS				
Front:	2 front panel attenuators, crossover select switch for HPF, Normal and LPF			
INDICATOR LEADS:	Five LED indicators per channel: Active, Signal, ACL, Temperature and DC			
Protection	Thermal, DC, subsonic, incorrect loads, under and over voltage			
CONNECTORS				
Inputs:	Dual combination 1/4" XLR	Dual combination 1/4" XLR	Dual combination 1/4" XLR	Dual combination 1/4" XLR
Outputs:	Dual 1/4" thru, one 2-pin & one 4-pin twist-lock connector	Dual 1/4" thru, one 2-pin & one 4-pin twist-lock connector	Three 4-pin twist lock connectors for 2 channels plus bridge	Three 4-pin twist lock connectors for 2 channels plus bridge
Construction	0.062" thick aluminum	0.062" thick aluminum	18 ga. galvanized steel	18 ga. galvanized steel
DIMENSIONS	3.5" x 19" x 17.25" behind front panel + 0.6" for handle	3.5" x 19" x 17.25" behind front panel + 0.6" for handle	3.5" x 19" x 17.25" behind front panel + 0.6" for handle	3.5" x 19" x 17.25" behind front panel + 0.6" for handle
Gross Weight	18.4 lbs* (8.34 kg)	17.4 lbs* (7.9 kg)	12.2 lbs* (5.54 kg)	10.9 lbs (4.94 kg)
Net Weight	14.6 lbs (6.61 kg)	13.6 lbs (6.2 kg)	13.9 lbs (6.30 kg)	13.3 lbs (6.02 kg)

Rated power readings made with BW: 20 Hz to 22 kHz. All power measurements made @ 120 VAC or 240VAC.

2 ohm steady state sine wave power is time limited by circuit breaker.

Bridge operation is not possible.

*Net Weight does not include power cord

Architect's & Engineer's Specifications



Features and specifications subject to change without notice.

Peavey Electronics Corporation • 5022 Hartley Peavey Drive • Meridian, MS 39305
Phone: (601) 483-5365 • Fax: (601) 486-1278 • www.peaveycommercialaudio.com



Commercial Audio