

SP® 15M



OVERVIEW

The SP® 15M two-way, full-range floor monitor features a 15" BWX Black Widow® 4" diameter VC woofer with a field-replaceable basket, RX™ 22CT compression driver with titanium diaphragm, and Sound Guard™ III tweeter protection. The unit includes dual-baffle angles of 45° or 30° and two 1/4" full-range phone-jack inputs in parallel with a four-pin twist lock connector.

FEATURES

- Two-way, full-range floor monitor
- 1,000 watts program, 2,000 watts peak
- BWX Black Widow® woofer, 4" VC, field-replaceable basket
- RX™22CT compression driver with titanium diaphragm
- Sound Guard™ III tweeter protection
- Dual-baffle angles of 45° or 30°
- Two 1/4" full range phone-jack inputs in parallel with a four-pin twist lock connector
- Metal stand mount adapter incorporated and four rubber feet on side for angle use
- Plywood enclosure finished in black textured paint
- Full length black powder coated metal grille
- Weight Unpacked: 58.42 lb(26.5 kg)
- Weight Packed: 62.83 lb(28.5 kg)
- Width Packed: 25"(63.5 cm)
- Height Packed: 27.166"(69.00164 cm)
- Depth Packed: 15.75"(40.005 cm)